Flight manual DG-500/22 ELAN

0.1 Record of revisions

Any revision of the present manual, except actual weighing data, must be recorded in the following table and in case of approved sections endorsed by the responsible airworthiness authority.

The new or amended text in the revised page will be indicated by a black vertical line in the right hand margin, and the Revision No. and the date will be shown on the bottom left hand of the page.

Rev.	Affected pages /	Description	Issue	LBA	Inserted
No.	section		Date	Approval	Date
				Date	Signature
1	0.3, 4.11	TN 348/1S	Mar. 92	31.03.92	
2	0.4,7.2	TN 348/3S	Oct. 92	08.12.92	
3	0.3, 0.4, 1.2, 2.5,	TN 348/9	Oct. 97	26.11.97	
	4.3, 5.2, 5.5, 6.2,				
	6.5, 6.7, 6.9, 7.1,				
	7.9, 7.10				
4	0.3, 0.4, 4.7, 7.7,	TN 348/15	Jan. 01	07.02.01	
	8.2				
Rev.	Affected pages /	Description	Issue	EASA	Inserted
No.	section		Date	Approval	Date
				Date	Signature
5	0.3, 0.4, 2.6, 3.1-	TN 348/20	May	August 1.	
	3.4, 4.1, 4.7,	manual revision	2008	2008	
	4.15, 7.1, 7.7, 7.8				
6	0.3, 0.4, 9.1, 9.2	Special equip-	May	20.07.	
		ment for very	2010	2010	
		small pilots			
		TN500/02			

Issued: May 2010 TN500/02 0.1

0.2 List of effective pages

Section		page	issued	replaced replaced
0		0.0	May 90	
		0.1		of revisions
		0.2	See record	of revisions
		0.3		of revisions
		0.4		of revisions
		0.5	May 90	
1		1.1	II .	
Т		1.2	Dec.90	Oct. 97
		1.3	May 90	000. 37
		1.4	"	
		1.5	II	
2	App.	2.1	"	
	"	2.2	"	
	"	2.3	"	
	"	2.4	II II	0.7
	"	2.5 2.6	"	Oct. 97
	11	2.7	II .	May 08
	11	2.8	II	
	п	2.9	II .	
		2.,,		
3	II	3.1	II .	May 08
	11	3.2	II .	May 08
	II	3.3	II	May 08
	11	3.4	II .	May 08
4	11	4 1	11	74. 00
4	"	4.1	"	May 08
		4.2 4.3		Oct. 97
	11	4.4	11	OCC. 97
	"	4.5	II.	
	II	4.6	11	
	11	4.7	II .	Jan. 01 May 08
	II .	4.8	II .	
	11	4.9	11	
	11	4.10	II .	
	App.	4.11	"	March 92
	п	4.12	II .	
	11	4.13	II	
	"	4.14	"	00
	"	4.15	II 0.0	May 08
	"	4.16	May 90	

0.2 List of effective pages (cont.)

Section	page	issued	replaced	replaced
5 "	5.1 5.2	May 90	Oct. 97	
II	5.3	п	000. 57	
App.	5.4 5.5	11 11	Oct. 97	
	5.6	п	000. 37	
	5.7	"		
6	6.1	II .		
	6.2 6.3	"	Oct. 97	
	6.4	II		
	6.5	"	Oct. 97	
	6.6 6.7	" "	Oct. 97	
	6.8	п		
	6.9	"	Oct. 97	
-	П 1		0 1 05	
7	7.1 7.2	" "	Oct. 97 Oct. 92	May 08
	7.3	II .		
	7.4 7.5	" "		
	7.6	п		
	7.7	II	Jan. 01	May 08
	7.8 7.9	 H	May 08 Oct. 97	
	7.10	Oct. 97		
8	8.1 8.2	May 90	Jan. 01	
	8.3	II	Uaii. Ui	
	8.4	"		
	8.5	11		
9	9.1	May 90	Mai 10	
	9.2	May 10	1101 10	

Flight manual DG-500

9. Supplements

_> \ > \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
Section		page
9.1	Introduction	9.1
9.2	List of inserted supplements	9.1
9.3	Special equipment for very small pilots	9.2

9.1 Introduction

This section contains the appropriate supplements necessary to safely and efficiently operate the sailplane when equipped with various optional systems and equipment not provided with the standard sailplane.

9.2 List of inserted supplements

Date of	Document No.	Title of the inserted supplement
insertion		
May 2010	Section 9.3	Special equipment for very small pilots
		TN500/02

Issued: May 2010 TN500/02 9.1

Flight manual DG-500

9.3 Special equipment for very small pilots (TN500/02)

To facilitate the operation of the glider by very small pilots 3 different items have been developed, which may be used separately or together.

9.3.1 Removable seat back for the front seat

- a) Installation of the seat back: Install the seat back with 2 screws M6x16 DIN965 4.8 BIC with cup washers 15 x M6 MS NI NR4157 to the threads which have been installed according to working instruction No. 1 for TN500/02.
- b) The seat back may be adjusted further to the front by part Z198. Fix the part to the Velcro straps installed at the rear of the seat back.
- c) Remove the head rest from the seat (screwed connection) and install a head cushion 8R80/2 to the Velcro straps installed at the front of the seat back. When removing the seat back reinstall the headrest.

9.3.2 Airbrake-pushrod with additional handle in front cockpit

For pilots with arms too short to lock the airbrakes an airbrake-pushrod with additional handle part 5St69/2 may be instead in the front cockpit according to working instruction No. 2 for TN500/02 instead of part 5St69.

This part may remain in the glider for normal operation.

9.3.3 Rudder pedal plates for rear cockpit Z197

Pilots with very short legs may clip rudder pedal plates part no. Z197 on to the rudder pedals. Plates may be installed and removed as often as desired.

Issued: May 2010 TN500/02 9.2