

Subject	:	Fuel hoses, new types, increase of life time
Effectivity	:	Type: DG-800, variants: DG-800A,LA, DG-800B, all Ser. No.s Type: DG-500, variants: DG-500M, DG-500MB, all Ser. No.s Type: DG single seaters, variants: DG-400, DG-600M, all Ser. No.s
Accomplishment	:	<p>Instruction 1a: Inspection of the fuel hoses in the fuselage if installed from beginning of 2015 on prior to next engine use, latest within 4 weeks after publication of this TN.</p> <p>Instruction 1b: Inspection of the fuel hoses in the fuselage if installed prior to beginning of 2015 prior to the next 25 hour inspection or prior to the next annual inspection, whichever comes first.</p> <p>Instruction 2 and 3: If failures have been detected (Inspection according to instructions 1): Replacement of the fuel hoses within 2 weeks after the inspection. If no failures have been detected: Replacement of the fuel hoses latest when the installed fuel hoses have reached their life time limit and must be exchanged.</p> <p>Instruction 4: Annually after fuel hoses according to instructions 2 and 3 have reached a life time of 6 years resp. 3 years concerning the fuel hoses which are routed in front of the cylinder heads in variants DG-400 and DG-800A,LA.</p> <p>Instruction 5: Prior to exchanging fuel hoses, within 4 weeks after publication of this TN.</p>
Reason	:	<ol style="list-style-type: none">1. During service and annual inspections DG found that some fuel hoses with textile fabric covering installed from beginning of the year 2015 became weak or untight with time. This type of fuel hoses is installed inside the fuselage, not in the engine area where hoses with metal fabric shields are used. Weak hoses may kink and limit the fuel supply rate.2. Fuel hoses type DIN 73379-2A are of much better quality and easier to inspect as they have no lining. With this type of hoses DG has very good experience with the DG-1000M. When exchanging the textile fabric covered hoses against this type of hoses combined with periodically inspections the life time of the hoses may be increased to 10 years.3. Problems as described under 1. have not been found with fuel hoses with metal fabric shield used in the engine area. However these hoses should be replaced by fire resistant fuel hoses ISO 7840-A1 without lining to increase the life time to 10 years similar to item 2.4. Only DG-500M: In maintenance manual diagram the oil return line from the diaphragm fuel pump to the fuel tank and the plugged piece of hose at this pump were missing. This problem will be solved by a further manual revision.
Instructions	:	<ol style="list-style-type: none">1a + 1b Inspection of the fuel hoses in the fuselage. To accomplish this baggage compartment floors and rear wall must be removed. Check for kinked fuel hoses and wet fabric covering of the hoses. If one or both of these failures are found all fuel hoses with textile fabric covering must be replaced.2. Replace all fuel hoses in the fuselage by fuel hoses according to DIN 73379-2A following the fuel system diagrams issued with this TN. Caution: Only fuel hoses according to DIN 73379-2A are acceptable for installation. It is prohibited to install the previously used type of fuel hoses. Note: Fuel lines marked with "COH-Line 2134" supplied by DG Flugzeugbau meet the specification DIN 73379-2A.

If there are any plastic hose connectors replace them by metal hose connectors as given in the diagrams. Life time of these hoses may be increased to 10 years, see instruction 4.

DG-500M, DG-500MB, DG-600M and DG-800A,LA, DG-800B up to serial No. 8-102: Replace the 6mm fitting at the inlet of the electrical fuel pump by an 8mm fitting SAG08/R 1/8" MS.

DG-800B with permanently installed refuelling pump and fuel return line: Replace further fuel lines and hose connectors according to installation plan 8EP29 (attached to the MM) in addition to the above mentioned diagrams.

3. Replace all fuel hoses at the engine by fire resistant fuel hoses according to ISO 7840-A1 following the fuel system diagrams issued with this TN. If there are any plastic hose connectors replace them by metal hose connectors as given in the diagrams. Life time may be increased to 10 years, see instruction 4.

Caution: Only fuel hoses according to ISO 7840-A1 are acceptable for installation. It is prohibited to install the previously used type of fuel hoses.

DG-800B: For installation of these hoses see working instruction No. 1 for TN 800-44 in addition to the manual diagrams.

DG-800B and DG-500M: Enlarge the holes for the fuel hoses in the fire wall to dia. 19 mm. Install rubber sleeves DG part No. 60510523 in the holes.

Note for instruction 2 and 3: Any springs which may have been installed to prevent kinking of the hoses are no more necessary.

4. Increase life time of fuel hoses according to instructions 2 and 3 to 10 years. Change the "Summary of operating hours" of your motorglider accordingly. Inspect thoroughly and completely all fuel hoses visually for any damage especially fissures, kinks or leaks after the fuel hoses have reached a life time of 6 years resp. 3 years concerning the fuel hoses which are routed in front of the cylinder heads in variants DG-400 and DG-800A,LA. For the check switch on the ignition to run the electric fuel pump to demonstrate operating fuel pressure. Repeat this inspection every following year.
5. Exchange the following manual pages against new pages issued October 2016 marked with TN800/44, 500/10 resp. DG-SS-02. Respect the changes marked in the right hand margin.

MM DG-800 (for DG-800A,LA): 0.1, 0.3 – 0.6, 0.8, 0.11, 3.4, 3.7, 3.8, 8.2, diagram 11

MM DG-800B (Solo engine): 0.1, 0.3 - 0.7, 0.12, 0.13, 3.6, 3.10, 8.2, 8.3, diagrams 11, 11a, 11b, 11d, 8EP29 (file behind 8EP25), working instruction No. 1 for TN 800/44 (file at the end of the MM)

MMDG-800B (MW engine): 1 - 5, 43, 44, 47, 92, diagram 11

MM DG-500M Revision 3: 0.1, 0.3, 0.4, 0.6, 0.10, 0.11, 3.4, 3.6, 3.9, diagram 14

MM DG-500M Revision 4: 0.1, 0.6, 0.10, diagram 14

MM DG-500MB: 0, 1a, 2 - 5, 48, 52, 92, diagram 14

MM DG-400: 0.1, 0.3 – 0.6, 0.9, 0.12, 3.3, 3.6, 3.7, 8.2, diagram 8, delete diagram 8a

MM DG-600M: 0.1, 0.3 – 0.6, 0.11, 3.4, 3.7, 8.2, diagram 11

- Material : Manual pages see instruction 5
- Fuel hoses and hose clamps as given in the respective fuel system diagrams.
Material sets see MM section 8.
- In addition if necessary: Metal hose connectors to replace plastic hose connectors as given in the respective fuel system diagrams:
- | | |
|------------------------|----------------------|
| GS6 St | DG part No. 60000220 |
| GRS 8-6 St | DG part No. 60000221 |
| TS6 St | DG part No. 60000222 |
| TRS 8-6-8 St | DG part No. 60000225 |
| TSV8 St | DG part No. 60000226 |
| Nipple SAG08/R 1/8" MS | DG part No. 60507563 |
- DG-800B and DG-500M:** 2 rubber sleeves DG part No. 60510523
- DG-800B with permanently installed refuelling pump and fuel return line:**
TRS 6-8-6 St DG part No. 60507566
- Weight and balance : influence negligible
- Remarks : Instructions No. 1 and 5 may be executed by the pilot/owner himself.
The correct implementation of instructions 1 and 5 is to be inspected and entered in the aircraft logs by the pilot/owner.
- Instruction No. 2, 3 and 4:
1. EASA countries: The actions have to be performed according to the regulations of the Part M in an approved maintenance organisation and released according to M.A.801.
 2. Non EASA countries: The actions have to be performed in a licensed workshop. All instructions are to be inspected and entered in the aircraft logs by a licensed inspector.

Bruchsal, date:
9. November 2016
Revision 1
3. May 2017

Author: Modifications (initial issue) approved by EASA Date 02 December 2016
under Approval No. 10060297
Modifications (Revision 1) approved by EASA Date 4. July 2017
under Approval No. 10062513

Wilhelm 